

Part number

# MHON 10.25



Hood, LS-TYPE series, with 4 pegs, M25 side cable entry, size "57.27"

#### Product description

|                     |                         |
|---------------------|-------------------------|
| <b>Product type</b> | Hood                    |
| <b>Series</b>       | LS-TYPE                 |
| <b>Closing type</b> | With 4 pegs             |
| <b>Size</b>         | Size 57.27              |
| <b>Cable entry</b>  | Side cable entry<br>M25 |

#### Technical data

**IP degree of protection** IP65

#### Further technical details

|   |                |
|---|----------------|
| <b>Weight</b>                                 | 120,00 g       |
| <b>Operating temperature range (min, max)</b> | -40°C...+125°C |

#### Material properties

|                              |                |
|------------------------------|----------------|
| <b>Colour</b>                | RAL 9005 black |
| <b>RoHs conformity</b>       | Compliant      |
| <b>China RoHs - EFUP</b>     | E              |
| <b>REACH SVHC substances</b> | No             |

#### Approvals / Standards

|                       |         |
|-----------------------|---------|
| <b>Certifications</b> | DNV, BV |
| <b>UL</b>             | ECBT2   |
| <b>cUL</b>            | ECBT8   |

#### General ordering information

|                   |               |
|-------------------|---------------|
| <b>EAN13 code</b> | 8015747194242 |
| <b>eCl@ss 8.1</b> | 27440202      |
| <b>ETIM 7.0</b>   | EC000437      |


#### Packaging Information

|                                  |                   |
|----------------------------------|-------------------|
| <b>Sub-packaging weight</b>      | 0,60 kg           |
| <b>Sub-packaging description</b> | Plastic packaging |
| <b>Sub-packaging quantity</b>    | 5 Pcs             |
| <b>Sub-packaging EAN barcode</b> | 8015747195140     |

# Part number MHON 10.25



Catalogue drawings



Catalogue drawings

**CH..N - MA, MF..N enclosures** size "57.27" **LS-TYPE version**

| inserts:                   | page                      | housings with double lever | hoods with 4 pegs |
|----------------------------|---------------------------|----------------------------|-------------------|
| CDD .....                  | 42 poles + ⊕ 61 *         |                            |                   |
| CQE .....                  | 18 poles + ⊕ 81 *         |                            |                   |
| CSH .....                  | 10 poles + ⊕ 89 *         |                            |                   |
| CCE .....                  | 10 poles + ⊕ 90 *         |                            |                   |
| CNE, CSE, JONE, JCSE ..... | 10 poles + ⊕ 97 and 107 * |                            |                   |
| CSS .....                  | 10 poles + ⊕ 119 *        |                            |                   |
| CTE, CTSE **) .....        | 10 poles + ⊕ 127 *        |                            |                   |
| CMSE .....                 | 3+2 (aux) poles + ⊕ 135 * |                            |                   |
| CMCE .....                 | 3+2 (aux) poles + ⊕ 134 * |                            |                   |
| CX .....                   | 8/24 poles + ⊕ 151 *      |                            |                   |
| MIXO .....                 | 3 modules 160+195 *       |                            |                   |

insert centre distance: 57 x 27 mm

\* refer to catalogue page CN.12

| description  | part no.             |  | entry |                      |
|--|----------------------|--|-------|----------------------|
|  |                      |  | M     | M                    |
| bulkhead mounting housing, with 2 levers                   | <b>CHIN 10</b>       |  |       |                      |
| surface mounting housing, high construction, with 2 levers | <b>MAPN 10.32 32</b> |  |       |                      |
| with pegs, side entry                                      |                      |  |       | <b>MHON 10.25 25</b> |
| with pegs, side entry, high construction                   |                      |  |       | <b>MFON 10.32 32</b> |
| with pegs, top entry                                       |                      |  |       | <b>MHVN 10.25 25</b> |
| with pegs, top entry, high construction                    |                      |  |       | <b>MFVN 10.32 32</b> |

\*\*) only in the CHIN 10 enclosure

panel cut-out for bulkhead mounting housing in mm

- kiln powder coating with RAL 9005 black epoxy polyester powder  
- RAL 9005 black self-extinguishing thermoplastic locking lever (spare lever page 12)

dimensions shown are not binding and may be changed without notice

dimensions in mm

**CHIN 10**

**MAPN 10.32**

dimensions in mm

**MFON 10.32**

**MFVN 10.32**

**MHON 10.25**

**MHVN 10.25**