

Part number

# MHVN 24 G32



Hood, LS-TYPE series, with 2 levers, M32 top cable entry, size "104.27"

#### Product description

<b>Product type</b>	Hood
<b>Series</b>	LS-TYPE
<b>Closing type</b>	With 2 levers
<b>Size</b>	Size 104.27
<b>Cable entry</b>	Top cable entry M32

#### Technical data

**IP degree of protection** IP65

#### Further technical details

**Weight** 248,00 g

**Operating temperature range (min, max)** -40°C...+125°C

#### Material properties

<b>Other materials</b>	Lever: Polyamide (PA) Gasket: NBR
<b>Colour</b>	RAL 9005 black
<b>RoHs conformity</b>	Compliant
<b>China RoHs - EFUP</b>	E
<b>REACH SVHC substances</b>	No

#### Approvals / Standards

<b>Certifications</b>	DNV, BV
<b>UL</b>	ECBT2
<b>cUL</b>	ECBT8

#### General ordering information

<b>EAN13 code</b>	8015747194402
<b>eCl@ss 8.1</b>	27440202
<b>ETIM 7.0</b>	EC000437

#### Packaging Information

<b>Sub-packaging weight</b>	1,24 kg
<b>Sub-packaging description</b>	Plastic packaging
<b>Sub-packaging quantity</b>	5 Pcs
<b>Sub-packaging EAN barcode</b>	8015747194419

# Part number MHVN 24 G32



Catalogue drawings



Catalogue drawings

**CH..N - MF..N enclosures**      size "104.27"      LS-TYPE version

<p>inserts:      page</p> <p>CD ..... 64 poles + @ 51+53 *</p> <p>CDD ..... 108 poles + @ 64+66 *</p> <p>CQE ..... 46 poles + @ 83+85 *</p> <p>CSH ..... 24 poles + @ 91+93 *</p> <p>CCE ..... 24 poles + @ 100+104 *</p> <p>CNE, CSE, JONE, JCSE 24 poles + @ 101 and 109 *</p> <p>CSS ..... 24 poles + @ 121+123 *</p> <p>CMSE ..... 10+2 (aux) poles + @ 139 *</p> <p>CMCE ..... 10+2 (aux) poles + @ 138 *</p> <p>CX ..... 4/8 poles + @ 155 *</p> <p>MIXO ..... 6 modules 160+195 *</p> <p>insert centre distance: <b>104 x 27 mm</b></p> <p>* refer to catalogue page CN.12</p>	<p><b>hoods with 4 pegs</b></p>	<p><b>covers</b></p>
description	part no.      entry	part no.
with 2 levers and gasket, top entry with 2 levers and gasket, top entry, high construction	<b>MHVN 24 G32</b> <b>32</b> <b>MFVN 24 G32</b> <b>32</b>	
covers with pegs covers with 2 levers		<b>CHCN 24</b> <b>CHCN 24 G</b>
<p>dimensions in mm</p> <p><b>MHVN 24 G32</b></p> <p><b>MFVN 24 G32</b></p> <p>- kiln powder coating with RAL 9005 black epoxy polyester powder - RAL 9005 black self-extinguishing thermoplastic locking lever (spare lever page 12)</p> <div style="text-align: center; margin-top: 20px;"> </div> <p style="font-size: 8px;">dimensions shown are not binding and may be changed without notice</p>	<p>dimensions in mm</p> <p><b>CHCN 24</b></p> <p><b>CHCN 24 G</b></p>	