

Part number

MZAV 15 L25



Hood, IL-BRID series, with 2 pegs, M25 top cable entry, size "49.16", high construction

Product description

| | |
|----------------------|----------------------------------|
| Product type | Hood |
| Series | IL-BRID |
| Closing type | With 2 pegs |
| Size | Size 49.16 |
| Cable entry | Top cable entry with adapter M25 |
| Specification | High construction |

Technical data

IP degree of protection IP66 / IP67 / IP69

Further technical details

| | |
|---|----------------|
| Weight | 157,00 g |
| Operating temperature range (min, max) | -40°C...+125°C |

Material properties

| | |
|------------------------------|--|
| Other materials | Gasket: NBR |
| Colour | RAL 7040 grey |
| RoHs conformity | Compliant with exemption 6(c): copper alloy containing up to 4% lead by weight |
| China RoHs - EFUP | 50 |
| REACH SVHC substances | Yes Lead |
| SCIP number | 15deaf78-e939-4401-a0b0-e2228ca32a03 |

Approvals / Standards

| | |
|------------|-------|
| UL | ECBT2 |
| cUL | ECBT8 |

General ordering information

| | |
|-------------------|---------------|
| EAN13 code | 8015747060127 |
| eCl@ss 8.1 | 27440202 |
| ETIM 7.0 | EC000437 |

Packaging Information

| | |
|----------------------------------|----------------------|
| Packaging length | 225,00 mm |
| Packaging height | 130,00 mm |
| Packaging width | 150,00 mm |
| Packaging weight | 1,72 kg |
| Packaging volume | 4,39 dm ³ |
| Packaging description | Carton box |
| Packaging quantity | 10 Pcs |
| Packaging EAN code | 8015747251334 |
| Sub-packaging weight | 0,86 kg |
| Sub-packaging description | Plastic packaging |
| Sub-packaging quantity | 5 Pcs |
| Sub-packaging EAN barcode | 8015747251341 |


Part number

MZAV 15 L25




Catalogue drawings


CZOW L MZOW L



CZAOW L - MZAOW L CZAVV L - MZAVV L



CZVW L MZVW L



CZCW LG

