


Part number

# PE 3264 PI



Flush-mounting socket outlet, PLUSO series, 3 poles + PE, 6 h (red), 32 A, 380 ÷ 415 V, inclined

| Product description                           |   | Material properties          |   |
|---|---|------------------------------|---|
| <b>Product type</b>                           | Socket<br>Flush-mounting  | <b>Colour</b>                | RAL 7035 grey, RAL 3000 red   |
| <b>Series</b>                                 | PE...PI, PLUSO  | <b>RoHs conformity</b>       | Compliant with exemption<br>6(c): copper alloy containing up to 4% lead by weight |
| <b>N. of poles</b>                            | 3 poles +  | <b>China RoHs - EFUP</b>     | 50  |
| <b>Clock position</b>                         | 6   | <b>REACH SVHC substances</b> | Yes<br>Lead   |
| <b>Size</b>                                   | Socket fixing centre distance 77 x 85 mm  | <b>SCIP number</b>           | Ca7de37f-add8-4b77-9861-279c94903ade  |
| <b>Specification</b>                          | Inclined  | Approvals / Standards        |   |
| Technical data                                |   | <b>Reference standard</b>    | EN 60309-1 and -2   |
| <b>Current</b>                                | 32 A  | General ordering information |   |
| <b>Voltage</b>                                | 380 ÷ 415 V   | <b>EAN13 code</b>            | 8015747067294   |
| <b>IP degree of protection</b>                | IP44  | Packaging Information        |   |
| Further technical details                     |   | <b>Packaging length</b>      | 330,00 mm   |
| <b>Weight</b>                                 | 202,00 g  | <b>Packaging height</b>      | 175,00 mm   |
| <b>Operating temperature range (min, max)</b> | -25°C ... +40°C   | <b>Packaging width</b>       | 295,00 mm   |
|   |   | <b>Packaging weight</b>      | 2,50 kg   |
|   |   | <b>Packaging volume</b>      | 17,04 dm <sup>3</sup>   |
|   |   | <b>Packaging description</b> | Carton box  |
|   |   | <b>Packaging quantity</b>    | 10 Pcs  |
|   |   | <b>Packaging EAN code</b>    | 8015747067300   |

Part number

# PE 3264 PI



Catalogue drawings

(16 / 32A) PE ... PI



| PE ... PI       | A  | B   | C   | D  | E  | F  | G  | H    | X  | Y  |
|-----------------|----|-----|-----|----|----|----|----|------|----|----|
| <b>16A</b> 2P+⊖ | 64 | 82  | 82  | 38 | 46 | 52 | 62 | 30   | 52 | 60 |
|                 | 64 | 82  | 82  | 42 | 47 | 57 | 65 | 28   | 52 | 60 |
|                 | 92 | 100 | 100 | 43 | 47 | 66 | 78 | 37,5 | 77 | 85 |
| <b>32A</b> 2P+⊖ | 92 | 100 | 100 | 40 | 55 | 68 | 76 | 35,5 | 77 | 85 |
|                 | 92 | 100 | 100 | 40 | 55 | 68 | 76 | 35,5 | 77 | 85 |
|                 | 92 | 102 | 102 | 43 | 55 | 74 | 86 | 39,5 | 77 | 85 |