


Part number

PEW 16123 PI



Flush-mounting socket outlet, PLUSO series, 2 poles + PE, 12 h (white), 16 A, inclined

Product description

| | |
|-----------------------|---|
| Product type | Socket Flush-mounting |
| Series | PEW...PI, PLUSO |
| N. of poles | 2 poles +  |
| Clock position | 12 |
| Specification | Inclined |

Technical data

| | |
|--------------------------------|------------------|
| Current | 16 A |
| Voltage | ins. transformer |
| IP degree of protection | IP67 |

Further technical details

| | |
|---|-----------------|
| Weight | 138,00 g |
| Operating temperature range (min, max) | -25°C ... +40°C |

Material properties

| | |
|------------------------------|--|
| Colour | RAL 7035 grey, RAL 9010 white |
| RoHs conformity | Compliant with exemption 6(c): copper alloy containing up to 4% lead by weight |
| China RoHs - EFUP | 50 |
| REACH SVHC substances | Yes Lead |
| SCIP number | Ca7de37f-add8-4b77-9861-279c94903ade |

Approvals / Standards

| | |
|---------------------------|-------------------|
| Reference standard | EN 60309-1 and -2 |
|---------------------------|-------------------|

General ordering information

| | |
|-------------------|---------------|
| EAN13 code | 8015747071543 |
|-------------------|---------------|

Packaging Information

| | |
|------------------------------|----------------------|
| Packaging length | 285,00 mm |
| Packaging height | 170,00 mm |
| Packaging width | 190,00 mm |
| Packaging weight | 1,60 kg |
| Packaging volume | 9,21 dm ³ |
| Packaging description | Carton box |
| Packaging quantity | 10 Pcs |
| Packaging EAN code | 8015747111881 |


Part number

PEW 16123 PI



Catalogue drawings

(16 / 32A) PEW ... PI



| PEW ... PI | A | B | C | D | E | F | G | H | I | X | Y |
|-----------------|----|-----|-----|----|----|-----|----|------|----|----|----|
| 16A 2P+⊕ | 65 | 82 | 83 | 48 | 35 | 70 | 50 | 29 | 58 | 52 | 60 |
| 3P+⊕ | 65 | 82 | 87 | 48 | 37 | 78 | 58 | 30 | 65 | 52 | 60 |
| 3P+N+⊕ | 90 | 100 | 102 | 50 | 38 | 86 | 66 | 35 | 75 | 77 | 85 |
| 32A 2P+⊕ | 90 | 100 | 116 | 50 | 50 | 92 | 68 | 37 | 78 | 77 | 85 |
| 3P+⊕ | 90 | 100 | 116 | 50 | 50 | 92 | 68 | 37 | 78 | 77 | 85 |
| 3P+N+⊕ | 90 | 100 | 118 | 50 | 50 | 100 | 73 | 42.5 | 86 | 77 | 85 |