


Part number

PEW 1625 SV



Mobile plug, PLUSO series, 3 poles + N + PE, 2 h (green), 16 A, > 50 V, straight

| Product description | | Material properties | |
|---|---|------------------------------|---|
| Product type | Plug Mobile | Colour | RAL 7035 grey, RAL 6017 green |
| Series | PEW...SV, PLUSO | RoHs conformity | Compliant with exemption 6(c): copper alloy containing up to 4% lead by weight |
| Connection type | Screw terminal connection | China RoHs - EFUP | 50 |
| N. of poles | 3 poles + N +  | REACH SVHC substances | Yes Lead |
| Clock position | 2 | SCIP number | Ca7de37f-add8-4b77-9861-279c94903ade |
| Specification | Straight | Approvals / Standards | |
| Technical data | | Reference standard | EN 60309-1 and -2 |
| Current | 16 A | General ordering information | |
| Voltage | > 50 V | EAN13 code | 8015747071765 |
| IP degree of protection | IP67 | Packaging Information | |
| Further technical details | | Packaging length | 255,00 mm |
| Weight | 190,00 g | Packaging height | 195,00 mm |
| Operating temperature range (min, max) | -25°C ... +40°C | Packaging width | 245,00 mm |
| | | Packaging weight | 2,17 kg |
| | | Packaging volume | 12,18 dm ³ |
| | | Packaging description | Carton box |
| | | Packaging quantity | 10 Pcs |
| | | Packaging EAN code | 8015747111904 |

Part number

PEW 1625 SV



Catalogue drawings

(16 / 32A) PEW ... SV



| PEW ... SV | | A | B | Pg Ø |
|------------|--------|-----|------|------|
| 16A | 2P+⊕ | 137 | 70 | 16 |
| | 3P+⊕ | 142 | 78 | 16 |
| | 3P+N+⊕ | 150 | 86 | 21 |
| 32A | 2P+⊕ | 170 | 92 | 21 |
| | 3P+⊕ | 170 | 92 | 21 |
| | 3P+N+⊕ | 175 | 99,5 | 21 |