


Part number

PEW 1635 PI



Flush-mounting socket outlet, PLUSO series, 3 poles + N + PE, 3 h (red), 16 A, 380 V, inclined

Product description

| | |
|-----------------------|---|
| Product type | Socket Flush-mounting |
| Series | PEW...PI, PLUSO |
| N. of poles | 3 poles + N +  |
| Clock position | 3 |
| Specification | Inclined |

Technical data

| | |
|--------------------------------|---------------------------------|
| Current | 16 A |
| Voltage | 220/380V (50Hz) 250/440V (60Hz) |
| IP degree of protection | IP67 |

Further technical details

| | |
|---|-----------------|
| Operating temperature range (min, max) | -25°C ... +40°C |
|---|-----------------|

Material properties

| | |
|---------------|-----------------------------|
| Colour | RAL 7035 grey, RAL 3000 red |
|---------------|-----------------------------|

Approvals / Standards

| | |
|---------------------------|-------------------|
| Reference standard | EN 60309-1 and -2 |
|---------------------------|-------------------|

General ordering information

| | |
|-------------------|---------------|
| EAN13 code | 8015747157056 |
|-------------------|---------------|

Part number

PEW 1635 PI



Catalogue drawings

(16 / 32A) PEW ... PI



| PEW ... PI | A | B | C | D | E | F | G | H | I | X | Y | |
|------------|--------|----|-----|-----|----|----|-----|----|------|----|----|----|
| 16A | 2P+⊕ | 65 | 82 | 83 | 48 | 35 | 70 | 50 | 29 | 58 | 52 | 60 |
| | 3P+⊕ | 65 | 82 | 87 | 48 | 37 | 78 | 58 | 30 | 65 | 52 | 60 |
| | 3P+N+⊕ | 90 | 100 | 102 | 50 | 38 | 86 | 66 | 35 | 75 | 77 | 85 |
| 32A | 2P+⊕ | 90 | 100 | 116 | 50 | 50 | 92 | 68 | 37 | 78 | 77 | 85 |
| | 3P+⊕ | 90 | 100 | 116 | 50 | 50 | 92 | 68 | 37 | 78 | 77 | 85 |
| | 3P+N+⊕ | 90 | 100 | 118 | 50 | 50 | 100 | 73 | 42.5 | 86 | 77 | 85 |