


Part number

PEW 3255 PI



Flush-mounting socket outlet, PLUSO series, 3 poles + N + PE, 5 h (black), 32 A, 347/600 ÷ 400/690 V, inclined

Product description

| | |
|-----------------------|---|
| Product type | Socket Flush-mounting |
| Series | PEW...PI, PLUSO |
| N. of poles | 3 poles + N +  |
| Clock position | 5 |
| Specification | Inclined |

Technical data

| | |
|--------------------------------|---------------------|
| Current | 32 A |
| Voltage | 347/600 ÷ 400/690 V |
| IP degree of protection | IP67 |

Further technical details

| | |
|---|-----------------|
| Weight | 280,00 g |
| Operating temperature range (min, max) | -25°C ... +40°C |

Material properties

| | |
|------------------------------|--|
| Colour | RAL 7035 grey, RAL 9005 black |
| RoHs conformity | Compliant with exemption 6(c): copper alloy containing up to 4% lead by weight |
| China RoHs - EFUP | 50 |
| REACH SVHC substances | Yes Lead |
| SCIP number | Ca7de37f-add8-4b77-9861-279c94903ade |

Approvals / Standards

| | |
|---------------------------|-------------------|
| Reference standard | EN 60309-1 and -2 |
|---------------------------|-------------------|

General ordering information

| | |
|-------------------|---------------|
| EAN13 code | 8015747075183 |
|-------------------|---------------|

Packaging Information

| | |
|------------------------------|-----------------------|
| Packaging length | 255,00 mm |
| Packaging height | 195,00 mm |
| Packaging width | 245,00 mm |
| Packaging weight | 2,90 kg |
| Packaging volume | 12,18 dm ³ |
| Packaging description | Carton box |
| Packaging quantity | 10 Pcs |
| Packaging EAN code | 8015747075190 |

Part number

PEW 3255 PI



Catalogue drawings

(16 / 32A) PEW ... PI



| PEW ... PI | A | B | C | D | E | F | G | H | I | X | Y | |
|------------|--------|----|-----|-----|----|----|-----|----|------|----|----|----|
| 16A | 2P+⊕ | 65 | 82 | 83 | 48 | 35 | 70 | 50 | 29 | 58 | 52 | 60 |
| | 3P+⊕ | 65 | 82 | 87 | 48 | 37 | 78 | 58 | 30 | 65 | 52 | 60 |
| | 3P+N+⊕ | 90 | 100 | 102 | 50 | 38 | 86 | 66 | 35 | 75 | 77 | 85 |
| 32A | 2P+⊕ | 90 | 100 | 116 | 50 | 50 | 92 | 68 | 37 | 78 | 77 | 85 |
| | 3P+⊕ | 90 | 100 | 116 | 50 | 50 | 92 | 68 | 37 | 78 | 77 | 85 |
| | 3P+N+⊕ | 90 | 100 | 118 | 50 | 50 | 100 | 73 | 42.5 | 86 | 77 | 85 |