


Part number

PK 12575 PB5



Interlocked switched socket-outlet, PK series,
3 poles + N + PE, 7 h (black), 125 A, 480 ÷
500 V, NH00 fuse carrier

Product description

Product type	Interlocked switched socket-outlet
Series	PK..PB5
N. of poles	3 poles + N + 
Clock position	7
Specification	NH00 fuse carrier

Technical data

Current	125 A
Voltage	480 ÷ 500 V
IP degree of protection	IP55

Further technical details

Weight	9.200,00 g
Operating temperature range (min, max)	-25°C ... +40°C
IK rating (impact degree of protection)	IK10

Material properties

Colour	RAL 7035 grey, RAL 9005 black
RoHs conformity	Compliant with exemption 6(c): copper alloy containing up to 4% lead by weight
China RoHs - EFUP	50
REACH SVHC substances	Yes Lead
SCIP number	Ce861c8d-b979-403b-96d9-80aef6dc281d

Approvals / Standards

Reference standard	EN 60309-1, -2 e -4
---------------------------	---------------------

General ordering information

EAN13 code	8015747079549
-------------------	---------------

Packaging Information

Packaging length	570,00 mm
Packaging height	200,00 mm
Packaging width	265,00 mm
Packaging weight	9,90 kg
Packaging volume	30,21 dm ³
Packaging description	Carton box
Packaging quantity	1 Pcs
Packaging EAN code	8015747079556
Sub-packaging length	113,00 mm
Sub-packaging height	36,00 mm
Sub-packaging width	180,00 mm
Sub-packaging volume	0,73 dm ³

Part number

PK 12575 PB5



Catalogue drawings

