

Part number

# PK 32114 EB



Interlocked switched socket-outlet, PK series,  
3 poles + PE, 11 h (red), 32 A, 440 ÷ 460 V,  
without fuse-carrier

## Product description

|                |                                                                                               |
|----------------|-----------------------------------------------------------------------------------------------|
| Product type   | Interlocked switched socket-outlet                                                            |
| Series         | PK..EB                                                                                        |
| N. of poles    | 3 poles +  |
| Clock position | 11                                                                                            |
| Specification  | Without fuse-carrier                                                                          |

## Technical data

|                         |             |
|-------------------------|-------------|
| Current                 | 32 A        |
| Voltage                 | 440 ÷ 460 V |
| IP degree of protection | IP44        |

## Further technical details

|                                         |                 |
|-----------------------------------------|-----------------|
| Weight                                  | 1.300,00 g      |
| Operating temperature range (min, max)  | -25°C ... +40°C |
| IK rating (impact degree of protection) | IK10            |

## Material properties

|                       |                                                                                |
|-----------------------|--------------------------------------------------------------------------------|
| Colour                | RAL 7035 grey, RAL 3000 red                                                    |
| RoHs conformity       | Compliant with exemption 6(c): copper alloy containing up to 4% lead by weight |
| China RoHs - EFUP     | 50                                                                             |
| REACH SVHC substances | Yes<br>Lead                                                                    |
| SCIP number           | F6799547-ab84-42f2-938f-233ba663766d                                           |

## Approvals / Standards

|                    |                     |
|--------------------|---------------------|
| Reference standard | EN 60309-1, -2 e -4 |
|--------------------|---------------------|

## General ordering information

|            |               |
|------------|---------------|
| EAN13 code | 8015747080927 |
|------------|---------------|

## Packaging Information

|                           |                      |
|---------------------------|----------------------|
| Sub-packaging length      | 290,00 mm            |
| Sub-packaging height      | 125,00 mm            |
| Sub-packaging width       | 155,00 mm            |
| Sub-packaging weight      | 1,30 kg              |
| Sub-packaging volume      | 5,62 dm <sup>3</sup> |
| Sub-packaging description | Carton box           |
| Sub-packaging quantity    | 1 Pcs                |
| Sub-packaging EAN barcode | 8015747080934        |

Part number

# PK 32114 EB



Catalogue drawings

