

Part number

TM 1633 SP



Interlocked switched socket-outlet, TM series, 2 poles + PE, 3 h (white), 16 A, 50 ÷ 250 V, without fuse-carrier, with base box

Product description	
Product type	Interlocked switched socket-outlet
Series	TM..SP/KSP
N. of poles	2 poles +
Clock position	3
Specification	Without fuse-carrier With base box
Technical data	
Current	16 A
Voltage	> 50 ÷ 250 V
IP degree of protection	IP66 / IP67
Further technical details	
Weight	1.310,00 g
Operating temperature range (min, max)	-25°C ... +40°C
UL 94 flammability rating	V-2
IK rating (impact degree of protection)	IK10

Material properties	
Colour	RAL 7012 grey, RAL 9010 white
RoHs conformity	Compliant with exemption 6(c): copper alloy containing up to 4% lead by weight
China RoHs - EFUP	50
REACH SVHC substances	Yes Lead
SCIP number	Ce861c8d-b979-403b-96d9-80aef6dc281d
Approvals / Standards	
Reference standard	EN 60309-1, -2 e -4
General ordering information	
EAN13 code	8015747161268
Packaging Information	
Packaging weight	11,79 kg
Packaging volume	52,36 dm ³
Packaging description	Carton box
Packaging quantity	9 Pcs
Packaging EAN code	8015747203180
Sub-packaging weight	1,31 kg
Sub-packaging description	Plastic packaging
Sub-packaging quantity	1 Pcs
Sub-packaging EAN barcode	8015747203197

Part number

TM 1633 SP



Catalogue drawings



	A	B
2P+⊕	133	276
3P+⊕	135	276
3P+N+⊕	140	277