

Part number

# TM 1643 IR



Interlocked switched socket-outlet, TM series, 2 poles + PE, 4 h (yellow), 16 A, 100 ÷ 130 V, with compartment for modular units, 4,5 DIN-rail modules EN 60715, with base box

Product description	
<b>Product type</b>	Interlocked switched socket-outlet
<b>Series</b>	TM..IR/KIR
<b>N. of poles</b>	2 poles +
<b>Clock position</b>	4
<b>Size</b>	115 x 450 x 18 mm
<b>Specification</b>	With compartment for modular units, 4,5 DIN-rail modules EN 60715 With base box

Technical data	
<b>Current</b>	16 A
<b>Voltage</b>	100 ÷ 130 V
<b>IP degree of protection</b>	IP66 / IP67

Further technical details	
<b>Weight</b>	1.310,00 g
<b>Operating temperature range (min, max)</b>	-25°C ... +40°C
<b>UL 94 flammability rating</b>	V-2
<b>IK rating (impact degree of protection)</b>	IK10

Material properties	
<b>Colour</b>	RAL 7012 grey, RAL 1021 yellow
<b>RoHs conformity</b>	Compliant with exemption 6(c): copper alloy containing up to 4% lead by weight
<b>China RoHs - EFUP</b>	50
<b>REACH SVHC substances</b>	Yes Lead
<b>SCIP number</b>	Ce861c8d-b979-403b-96d9-80aef6dc281d

Approvals / Standards	
<b>Reference standard</b>	EN 60309-1, -2 e -4

General ordering information	
<b>EAN13 code</b>	8015747089531

Packaging Information	
<b>Packaging weight</b>	12,35 kg
<b>Packaging volume</b>	52,36 dm <sup>3</sup>
<b>Packaging description</b>	Carton box
<b>Packaging quantity</b>	9 Pcs
<b>Packaging EAN code</b>	8015747089548
<b>Sub-packaging weight</b>	1,37 kg
<b>Sub-packaging description</b>	Plastic packaging
<b>Sub-packaging quantity</b>	1 Pcs
<b>Sub-packaging EAN barcode</b>	8015747089555

Part number

# TM 1643 IR



Catalogue drawings



	A	B
2P+ $\oplus$	133	276
3P+ $\oplus$	135	276
3P+N+ $\oplus$	140	277