


Part number

TM 1645 SIR



Interlocked switched socket-outlet, TM series, 3 poles + N + PE, 4 h (yellow), 16 A, 57/100 ÷ 75/130 V, with compartment for modular units, 4,5 DIN-rail modules EN 60715, without base box

Product description	
Product type	Interlocked switched socket-outlet
Series	TM..SIR/KSIR
N. of poles	3 poles + N + 
Clock position	4
Size	114 x 255 mm fixing distance, for assembly in single or multiple boxes
Specification	With compartment for modular units, 4,5 DIN-rail modules EN 60715 Without base box
Technical data	
Current	16 A
Voltage	57/100 ÷ 75/130 V
IP degree of protection	IP66 / IP67
Further technical details	
Weight	1.070,00 g
Operating temperature range (min, max)	-25°C ... +40°C
UL 94 flammability rating	V-2
IK rating (impact degree of protection)	IK10

Material properties	
Colour	RAL 7012 grey, RAL 1021 yellow
Approvals / Standards	
Reference standard	EN 60309-1, -2 e -4
General ordering information	
EAN13 code	8015747089722
Packaging Information	
Sub-packaging weight	1,07 kg
Sub-packaging description	Carton tray
Sub-packaging quantity	1 Pcs
Sub-packaging EAN barcode	8015747108423

Part number

TM 1645 SIR



Catalogue drawings



	A	B
2P+⊕	83	276
3P+⊕	85	276
3P+N+⊕	90	277