


Part number

TM 1675 SIT



Interlocked switched socket-outlet, TM series, 3 poles + N + PE, 7 h (black), 16 A, 277/480 ÷ 288/500 V, E16 fuse carrier, without base box

Product description	
Product type	Interlocked switched socket-outlet
Series	TM.. SIT
N. of poles	3 poles + N + 
Clock position	7
Specification	E16 fuse carrier Without base box
Technical data	
Current	16 A
Voltage	277/480 ÷ 288/500 V
IP degree of protection	IP66 / IP67
Further technical details	
Weight	1.300,00 g
Operating temperature range (min, max)	-25°C ... +40°C
UL 94 flammability rating	V-2
IK rating (impact degree of protection)	IK10


Material properties	
Colour	RAL 7012 grey, RAL 9005 black
Approvals / Standards	
Reference standard	EN 60309-1, -2 e -4
General ordering information	
EAN13 code	8015747090407
Packaging Information	
Sub-packaging weight	1,30 kg
Sub-packaging description	Carton tray
Sub-packaging quantity	1 Pcs
Sub-packaging EAN barcode	8015747108508

Part number

TM 1675 SIT



Catalogue drawings



	A	B
2P+⊕	83	276
3P+⊕	85	276
3P+N+⊕	90	277