


Part number

TM 3224 IT



Interlocked switched socket-outlet, TM series,
3 poles + PE, 2 h (green), 32 A, > 50 V, E33 -
DIII fuse carrier, with base box

Product description

Product type	Interlocked switched socket-outlet
Series	TM.. IT
N. of poles	3 poles + 
Clock position	2
Specification	E33 - DIII fuse carrier With base box

Technical data

Current	32 A
Voltage	> 50 V
IP degree of protection	IP66 / IP67

Further technical details

Weight	3.390,00 g
Operating temperature range (min, max)	-25°C ... +40°C
UL 94 flammability rating	V-2
IK rating (impact degree of protection)	IK10

Material properties

Colour	RAL 7012 grey, RAL 6017 green
RoHs conformity	Compliant with exemption 6(c): copper alloy containing up to 4% lead by weight
China RoHs - EFUP	50
REACH SVHC substances	Yes Lead
SCIP number	F6799547-ab84-42f2-938f-233ba663766d

Approvals / Standards

Reference standard	EN 60309-1, -2 e -4
---------------------------	---------------------

General ordering information

EAN13 code	8015747162395
-------------------	---------------

Packaging Information

Sub-packaging length	150,00 mm
Sub-packaging height	188,00 mm
Sub-packaging width	430,00 mm
Sub-packaging weight	3,39 kg
Sub-packaging volume	12,13 dm ³
Sub-packaging description	Carton box
Sub-packaging quantity	1 Pcs
Sub-packaging EAN barcode	8015747095044

Part number

TM 3224 IT



Catalogue drawings



	A
2P+⊕	162
3P+⊕	162
3P+N+⊕	169