


Part number

# TM 3234KIR



Interlocked switched socket-outlet, TM series, 3 poles + PE, 3 h (red), 32 A, 380 ÷ 380 V, with compartment for modular units, 4,5 DIN-rail modules EN 60715, with base box

| Product description                            |   | Material properties                 |  |
|--|---|-------------------------------------|--|
| <b>Product type</b>                            | Interlocked switched socket-outlet  | <b>Colour</b>                       | RAL 7012 grey, RAL 3000 red  |
| <b>Series</b>                                  | TM..IR/KIR  |                                     | Compliant with exemption 6(c): copper alloy containing up to 4% lead by weight |
| <b>N. of poles</b>                             | 3 poles +  | <b>RoHs conformity</b>              |  |
| <b>Clock position</b>                          | 3   | <b>China RoHs - EFUP</b>            | 50   |
| <b>Specification</b>                           | With compartment for modular units, 4,5 DIN-rail modules EN 60715<br>With base box          | <b>REACH SVHC substances</b>        | Yes<br>Lead  |
| <b>Technical data</b>                          |   | <b>SCIP number</b>                  | Ce861c8d-b979-403b-96d9-80aef6dc281d   |
| <b>Current</b>                                 | 32 A  | <b>Approvals / Standards</b>        |  |
| <b>Voltage</b>                                 | 380V (50Hz.) 440V (60Hz.)   | <b>Reference standard</b>           | EN 60309-1, -2 e -4  |
| <b>IP degree of protection</b>                 | IP66 / IP67   | <b>General ordering information</b> |  |
| <b>Further technical details</b>               |   | <b>EAN13 code</b>                   | 8015747162807  |
| <b>Weight</b>                                  | 1.410,00 g  | <b>Packaging Information</b>        |  |
| <b>Operating temperature range (min, max)</b>  | -25°C ... +40°C   | <b>Packaging length</b>             | 385,00 mm  |
| <b>UL 94 flammability rating</b>               | V-2   | <b>Packaging height</b>             | 320,00 mm  |
| <b>IK rating (impact degree of protection)</b> | IK10  | <b>Packaging width</b>              | 485,00 mm  |
|  |   | <b>Packaging weight</b>             | 12,69 kg   |
|  |   | <b>Packaging volume</b>             | 59,75 dm <sup>3</sup>  |
|  |   | <b>Packaging description</b>        | Carton box   |
|  |   | <b>Packaging quantity</b>           | 9 Pcs  |
|  |   | <b>Packaging EAN code</b>           | 8015747166300  |
|  |   | <b>Sub-packaging weight</b>         | 1,41 kg  |
|  |   | <b>Sub-packaging description</b>    | Carton tray  |
|  |   | <b>Sub-packaging quantity</b>       | 1 Pcs  |
|  |   | <b>Sub-packaging EAN barcode</b>    | 8015747166317  |

Part number

# TM 3234KIR



Catalogue drawings



|               | A   | B   |
|---------------|-----|-----|
| <b>2P+⊕</b>   | 133 | 276 |
| <b>3P+⊕</b>   | 135 | 276 |
| <b>3P+N+⊕</b> | 140 | 277 |