

Part number

TM 3243KSIR



Interlocked switched socket-outlet, TM series, 2 poles + PE, 4 h (yellow), 32 A, 100 ÷ 130 V, with compartment for modular units, 4,5 DIN-rail modules EN 60715, without base box

Product description	
Product type	Interlocked switched socket-outlet
Series	TM..SIR/KSIR
N. of poles	2 poles +
Clock position	4
Size	114 x 255 mm fixing distance, for assembly in single or multiple boxes
Specification	With compartment for modular units, 4,5 DIN-rail modules EN 60715 Without base box
Technical data	
Current	32 A
Voltage	100 ÷ 130 V
IP degree of protection	IP66 / IP67
Further technical details	
Weight	1.080,00 g
Operating temperature range (min, max)	-25°C ... +40°C
UL 94 flammability rating	V-2
IK rating (impact degree of protection)	IK10

Material properties	
Colour	RAL 7012 grey, RAL 1021 yellow
RoHs conformity	Compliant with exemption 6(c): copper alloy containing up to 4% lead by weight
China RoHs - EFUP	50
REACH SVHC substances	Yes Lead
SCIP number	Ce861c8d-b979-403b-96d9-80aef6dc281d
Approvals / Standards	
Reference standard	EN 60309-1, -2 e -4
General ordering information	
EAN13 code	8015747126434
Packaging Information	
Packaging length	385,00 mm
Packaging height	320,00 mm
Packaging width	485,00 mm
Packaging volume	59,75 dm ³
Packaging description	Plastic packaging
Packaging quantity	9 Pcs
Packaging EAN code	8015747271851
Sub-packaging length	95,00 mm
Sub-packaging height	40,00 mm
Sub-packaging width	253,00 mm
Sub-packaging volume	0,96 dm ³
Sub-packaging description	Carton tray
Sub-packaging quantity	1 Pcs
Sub-packaging EAN barcode	8015747271868

Part number

TM 3243KSIR



Catalogue drawings



	A
2P+⊕	96
3P+⊕	96
3P+N+⊕	101
