


Part number

TM 3263 ISX



Interlocked switched socket-outlet, TM ATEX series, 2 poles + PE, 6 h (blue), 32 A, 200 ÷ 250 V, sectionable fuse carrier 14 x 51 mm, with base box

| Product description | | Material properties | |
|--|---|----------------------------------|--|
| Product type | Interlocked switched socket-outlet | Colour | RAL 7012 grey, RAL 5015 blue |
| Series | TM ATEX | | Compliant with exemption 6(c): copper alloy containing up to 4% lead by weight |
| N. of poles | 2 poles +  | RoHs conformity | 6(c): copper alloy containing up to 4% lead by weight |
| Clock position | 6 | China RoHs - EFUP | 50 |
| Size | 144 x 370 mm fixing distance, for assembly in plates TM xx56 TB | REACH SVHC substances | Yes Lead |
| Specification | Sectionable fuse carrier 14 x 51 mm With base box | SCIP number | F6799547-ab84-42f2-938f-233ba663766d |
| Technical data | | Approvals / Standards | |
| Current | 32 A | Reference standard | EN 60309-1, -2 e -4 |
| Voltage | 200 ÷ 250 V | General ordering information | |
| IP degree of protection | IP66 / IP67 | EAN13 code | 8015747153522 |
| Further technical details | | Packaging Information | |
| Operating temperature range (min, max) | -25°C ... +40°C | Sub-packaging length | 150,00 mm |
| IK rating (impact degree of protection) | IK10 | Sub-packaging height | 188,00 mm |
| | | Sub-packaging width | 430,00 mm |
| | | Sub-packaging volume | 12,13 dm ³ |
| | | Sub-packaging description | Carton box |
| | | Sub-packaging quantity | 1 Pcs |
| | | Sub-packaging EAN barcode | 8015747210379 |