


Part number

TM 3293KSP



Interlocked switched socket-outlet, TM series,
2 poles + PE, 9 h (red), 32 A, 380 ÷ 415 V,
without fuse-carrier, with base box

Product description		Material properties	
Product type	Interlocked switched socket-outlet	Colour	RAL 7012 grey, RAL 3000 red
Series	TM..SP/KSP	RoHs conformity	Compliant with exemption 6(c): copper alloy containing up to 4% lead by weight
N. of poles	2 poles + 	China RoHs - EFUP	50
Clock position	9	REACH SVHC substances	Yes Lead
Size	115 x 450 x 18 mm	SCIP number	Ce861c8d-b979-403b-96d9-80aef6dc281d
Specification	Without fuse-carrier With base box	Approvals / Standards	
Technical data		Reference standard	EN 60309-1, -2 e -4
Current	32 A	General ordering information	
Voltage	380 ÷ 415 V	EAN13 code	8015747126229
IP degree of protection	IP66 / IP67	Packaging Information	
Further technical details		Packaging weight	12,33 kg
Weight	1.370,00 g	Packaging volume	55,44 dm ³
Operating temperature range (min, max)	-25°C ... +40°C	Packaging description	Carton box
UL 94 flammability rating	V-2	Packaging quantity	9 Pcs
IK rating (impact degree of protection)	IK10	Packaging EAN code	8015747114844
		Sub-packaging weight	1,37 kg
		Sub-packaging description	Carton tray
		Sub-packaging quantity	1 Pcs
		Sub-packaging EAN barcode	8015747044189

Part number

TM 3293KSP



Catalogue drawings



	A	B
2P+⊕	133	276
3P+⊕	135	276
3P+N+⊕	140	277