


Part number

# TM 3295KSIS



Interlocked switched socket-outlet, TM series, 3 poles + N + PE, 9 h (blue), 32 A, 120/208 ÷ 144/250 V, sectionable fuse carrier 10 x 38 mm, without base box

#### Product description

|                       |   |
|-----------------------|---|
| <b>Product type</b>   | Interlocked switched socket-outlet  |
| <b>Series</b>         | TM.. SIS/KSIS   |
| <b>N. of poles</b>    | 3 poles + N +  |
| <b>Clock position</b> | 9   |
| <b>Size</b>           | 114 x 255 mm fixing distance, for assembly in single or multiple boxes                          |
| <b>Specification</b>  | Sectionable fuse carrier 10 x 38 mm<br>Without base box   |

#### Technical data

|                                |                     |
|--------------------------------|---------------------|
| <b>Current</b>                 | 32 A                |
| <b>Voltage</b>                 | 120/208 ÷ 144/250 V |
| <b>IP degree of protection</b> | IP66 / IP67         |

#### Further technical details

|  |                 |
|--|-----------------|
| <b>Weight</b>                                  | 1.430,00 g      |
| <b>Operating temperature range (min, max)</b>  | -25°C ... +40°C |
| <b>UL 94 flammability rating</b>               | V-2             |
| <b>IK rating (impact degree of protection)</b> | IK10            |

#### Material properties

|               |                              |
|---------------|------------------------------|
| <b>Colour</b> | RAL 7012 grey, RAL 5015 blue |
|---------------|------------------------------|

#### Approvals / Standards

|                           |                     |
|---------------------------|---------------------|
| <b>Reference standard</b> | EN 60309-1, -2 e -4 |
|---------------------------|---------------------|

#### General ordering information

|                   |               |
|-------------------|---------------|
| <b>EAN13 code</b> | 8015747126335 |
|-------------------|---------------|

Part number

# TM 3295KSIS



## Catalogue drawings



|               | <b>A</b> |
|---------------|----------|
| <b>2P+⊕</b>   | 96       |
| <b>3P+⊕</b>   | 96       |
| <b>3P+N+⊕</b> | 101      |