


Part number

TM 6394 IT



Interlocked switched socket-outlet, TM series,
3 poles + PE, 9 h (blue), 63 A, 200 ÷ 250 V,
E33 - DIII fuse carrier, with base box

| Product description | |
|--|---|
| Product type | Interlocked switched socket-outlet |
| Series | TM.. IT |
| N. of poles | 3 poles +  |
| Clock position | 9 |
| Size | 145 x 565 x 18 mm |
| Specification | E33 - DIII fuse carrier With base box |
| Technical data | |
| Current | 63 A |
| Voltage | 200 ÷ 250 V |
| IP degree of protection | IP66 / IP67 |
| Further technical details | |
| Weight | 3.910,00 g |
| Operating temperature range (min, max) | -25°C ... +40°C |
| UL 94 flammability rating | V-0 (insert), V-2 (enclosure) |
| IK rating (impact degree of protection) | IK10 |

| Material properties | |
|----------------------------------|------------------------------|
| Colour | RAL 7012 grey, RAL 5015 blue |
| Approvals / Standards | |
| Reference standard | EN 60309-1, -2 e -4 |
| General ordering information | |
| EAN13 code | 8015747092838 |
| Packaging Information | |
| Sub-packaging weight | 3,91 kg |
| Sub-packaging description | Carton box |
| Sub-packaging quantity | 1 Pcs |
| Sub-packaging EAN barcode | 8015747108942 |

Part number

TM 6394 IT



Catalogue drawings

