


Part number

BP 6355



Cover with socket-outlet, BP series, 3 poles + N + PE, 5 h (black), 63 A, 347/600 ÷ 400/690 V

Product description

| | |
|-----------------------|---|
| Product type | Cover with socket-outlet |
| Series | BP |
| N. of poles | 3 poles + N +  |
| Clock position | 5 |

Technical data

| | |
|--------------------------------|---------------------|
| Current | 63 A |
| Voltage | 347/600 ÷ 400/690 V |
| IP degree of protection | IP67 |

Further technical details

| | |
|--|-----------------|
| Weight | 1.006,00 g |
| Operating temperature range (min, max) | -25°C ... +40°C |
| IK rating (impact degree of protection) | IK10 |

Material properties

| | |
|------------------------------|--|
| Colour | RAL 7035 grey, RAL 9005 black |
| RoHs conformity | Compliant with exemption 6(c): copper alloy containing up to 4% lead by weight |
| China RoHs - EFUP | 50 |
| REACH SVHC substances | Yes Lead |
| SCIP number | Ca7de37f-add8-4b77-9861-279c94903ade |

Approvals / Standards

| | |
|---------------------------|---------------------|
| Reference standard | EN 60309-1, -2 e -4 |
|---------------------------|---------------------|

General ordering information

| | |
|-------------------|---------------|
| EAN13 code | 8015747167789 |
|-------------------|---------------|

Packaging Information

| | |
|----------------------------------|----------------------|
| Sub-packaging length | 116,00 mm |
| Sub-packaging height | 130,00 mm |
| Sub-packaging width | 230,00 mm |
| Sub-packaging weight | 1,01 kg |
| Sub-packaging volume | 3,47 dm ³ |
| Sub-packaging description | Carton box |
| Sub-packaging quantity | 1 Pcs |
| Sub-packaging EAN barcode | 8015747191777 |