

Part number

# BP 6364



Cover with socket-outlet, BP series, 3 poles + PE, 6 h (red), 63 A, 380 ÷ 415 V

| Product description                     |                                                                                             | Material properties          |                                                                                |
|-----------------------------------------|---------------------------------------------------------------------------------------------|------------------------------|--------------------------------------------------------------------------------|
| Product type                            | Cover with socket-outlet                                                                    | Colour                       | RAL 7035 grey, RAL 3000 red                                                    |
| Series                                  | BP                                                                                          | RoHs conformity              | Compliant with exemption 6(c): copper alloy containing up to 4% lead by weight |
| N. of poles                             | 3 poles +  | China RoHs - EFUP            | 50                                                                             |
| Clock position                          | 6                                                                                           | REACH SVHC substances        | Yes                                                                            |
| Size                                    | Socket centre distance 114 x 228 mm                                                         | Lead                         | Lead                                                                           |
| Technical data                          |                                                                                             | SCIP number                  | Ca7de37f-add8-4b77-9861-279c94903ade                                           |
| Current                                 | 63 A                                                                                        | Approvals / Standards        |                                                                                |
| Voltage                                 | 380 ÷ 415 V                                                                                 | Reference standard           | EN 60309-1, -2 e -4                                                            |
| IP degree of protection                 | IP67                                                                                        | General ordering information |                                                                                |
| Further technical details               |                                                                                             | EAN13 code                   | 8015747005234                                                                  |
| Weight                                  | 946,00 g                                                                                    | Packaging Information        |                                                                                |
| Operating temperature range (min, max)  | -25°C ... +40°C                                                                             | Sub-packaging length         | 116,00 mm                                                                      |
| IK rating (impact degree of protection) | IK10                                                                                        | Sub-packaging height         | 130,00 mm                                                                      |
|                                         |                                                                                             | Sub-packaging width          | 230,00 mm                                                                      |
|                                         |                                                                                             | Sub-packaging weight         | 0,95 kg                                                                        |
|                                         |                                                                                             | Sub-packaging volume         | 3,47 dm <sup>3</sup>                                                           |
|                                         |                                                                                             | Sub-packaging description    | Carton box                                                                     |
|                                         |                                                                                             | Sub-packaging quantity       | 1 Pcs                                                                          |
|                                         |                                                                                             | Sub-packaging EAN barcode    | 8015747005258                                                                  |