

Part number

CCFJD 4.0



Female crimp contact, CC series, 16 A, turned gold plated, wire cross section 4 mm², AWG 12, basic gold plating

Product description

Product type	Crimp contact
Series	CC
Gender	Female
Specification	Basic gold plating

Technical data

Current	16 A
Wire cross-section	4,00 mm ²
AWG size	12
Contact type	Turned gold plated

Further technical details

Weight	1,60 g
Conductors stripping length	7,5 mm

Material properties

Main material	Copper alloy
RoHs conformity	Compliant with exemption 6(c): copper alloy containing up to 4% lead by weight
China RoHs - EFUP	50
REACH SVHC substances	Yes Lead
SCIP number	C0979fba-9907-458f-a94a-db781440f273

Approvals / Standards

Certifications	CSA, EAC
UL	ECBT2

General ordering information

EAN13 code	8015747074315
eCl@ss 8.1	27440204
ETIM 7.0	EC000796

Packaging Information


Packaging length	112,00 mm
Packaging height	95,00 mm
Packaging width	117,00 mm
Packaging weight	1,48 kg
Packaging volume	1,24 dm ³
Packaging description	Carton box
Packaging quantity	800 Pcs
Packaging EAN code	8015747207270
Sub-packaging length	50,00 mm
Sub-packaging height	44,00 mm
Sub-packaging width	50,00 mm
Sub-packaging weight	0,19 kg
Sub-packaging volume	0,11 dm ³
Sub-packaging description	Plastic box
Sub-packaging quantity	100 Pcs
Sub-packaging EAN barcode	8015747094016

Part number

CCFJD 4.0



Catalogue drawings



CCFJD and CCMJD contacts

conductor section mm ²	conductor slot $\varnothing A$ (mm)	conductors stripping length mm
0,14-0,37	0,9	7,5
0,5	1,1	7,5
0,75	1,3	7,5
1,0	1,45	7,5
1,5	1,8	7,5
2,5	2,2	7,5
3,0	2,55	7,5
4,0	2,85	7,5