

Part number

CCMC 0.5



Male crimp contact, CC series, 16 A, turned, constantan (Cu Ni), wire cross section 0,5 mm², AWG 20

| Product description | | Material properties | |
|------------------------------------|----------------------------|----------------------------------|----------------------|
| Product type | Crimp contact | RoHS conformity | Compliant |
| Series | CC | China RoHS - EFUP | E |
| Gender | Male | REACH SVHC substances | No |
| Technical data | | Approvals / Standards | |
| Current | 16 A | Certifications | CSA, EAC |
| Wire cross-section | 0,50 mm ² | General ordering information | |
| AWG size | 20 | EAN13 code | 8015747012454 |
| Contact type | Turned, constantan (Cu Ni) | eCl@ss 8.1 | 27440204 |
| Further technical details | | ETIM 7.0 | EC000796 |
| Weight | 1,40 g | Packaging Information | |
| Conductors stripping length | 7,5 mm | Sub-packaging length | 50,00 mm |
| | | Sub-packaging height | 44,00 mm |
| | | Sub-packaging width | 50,00 mm |
| | | Sub-packaging volume | 0,11 dm ³ |
| | | Sub-packaging description | Plastic box |
| | | Sub-packaging quantity | 5 Pcs |
| | | Sub-packaging EAN barcode | 8015747173209 |

Part number

CCMC 0.5



Catalogue drawings



CCF, CCM and CC..AN contacts

| conductor section mm ² | conductor slot $\varnothing A$ (mm) | conductors stripping length (mm) |
|--------------------------------------|--|-------------------------------------|
| 0,14-0,37 | 0,9 | 7,5 |
| 0,5 | 1,1 | 7,5 |
| 0,75 | 1,3 | 7,5 |
| 1,0 | 1,45 | 7,5 |
| 1,5 | 1,8 | 7,5 |
| 2,5 | 2,2 | 7,5 |
| 3 | 2,55 | 7,5 |
| 4 | 2,85 | 7,5 |