

Part number

CHIN 16



Bulkhead mounting housing, LS-TYPE series, with 2 levers, size "77.27"

Product description

Product type	Bulkhead mounting housing
Series	LS-TYPE
Closing type	With 2 levers
Size	Size 77.27
Cable entry	Without cable entry

Technical data

IP degree of protection	IP65
--------------------------------	------

Further technical details

Weight	95,00 g
Operating temperature range (min, max)	-40°C...+125°C

Material properties

Other materials	Lever: Polyamide (PA) Gasket: NBR
Colour	RAL 9005 black
RoHs conformity	Compliant
China RoHs - EFUP	E
REACH SVHC substances	No

Approvals / Standards

Certifications	DNV, BV
UL	ECBT2
cUL	ECBT8

General ordering information

EAN13 code	8015747163095
eCl@ss 8.1	27440202
ETIM 7.0	EC000437

Packaging Information

Packaging length	360,00 mm
Packaging height	165,00 mm
Packaging width	315,00 mm
Packaging weight	3,80 kg
Packaging volume	18,71 dm ³
Packaging description	Carton box
Packaging quantity	40 Pcs
Packaging EAN code	8015747187602
Sub-packaging weight	0,48 kg
Sub-packaging description	Plastic packaging
Sub-packaging quantity	5 Pcs
Sub-packaging EAN barcode	8015747187619

Part number CHIN 16



Catalogue drawings



Catalogue drawings

CH..N - MA, MF..N enclosures size "77.27" **LS-TYPE version**

inserts:	page	housings with double lever	hoods with 4 pegs
CD	40 poles + @ 49+52 *		
CT, CTS **)	40 poles + @ 56 *		
CDD	72 poles + @ 62+65 *		
CDE	32 poles + @ 82+84 *		
CSH	16 poles + @ 90+92 *		
CCE	16 poles + @ 98+102 *		
CNE, CSE, JCNE, JCSE	16 poles + @ 99 and 108 *		
CSS	16 poles + @ 120+122 *		
CTE, CTSE **)	16 poles + @ 128 *		
CMSE	6+2 (aux) poles + @ 137 *		
CMCE	6+2 (aux) poles + @ 136 *		
CP	6 poles + @ 149+150 *		
CX	6/36 e 12/2 poles + @ 152+153 *		
CX	4/0 e 4/2 poles + @ 154 *		
MIXO	4 modules 160-195 *		

insert centre distance: 77,5 x 27 mm
* refer to catalogue page CN.12

description	part no.	entry	part no.	entry
bulkhead mounting housing, with 2 levers	CHIN 16	M		
surface mounting housing, high construction, with 2 levers	MAPN 16.32	32		
with pegs, side entry			MHON 16.32	32
with pegs, side entry, high construction			MFON 16.32	32
with pegs, top entry			MHVN 16.32	32
with pegs, top entry, high construction			MFVN 16.32	32

**) only in the CHIN 16 enclosure

panel cut-out for bulkhead mounting housing in mm

- kiln powder coating with RAL 9005 black epoxy polyester powder
- RAL 9005 black self-extinguishing thermoplastic locking lever (spare lever page 12)

dimensions shown are not binding and may be changed without notice

dimensions in mm	dimensions in mm
CHIN 16	MFON 16.32
MAPN 16.32	MFVN 16.32
	MHON 16.32
	MHVN 16.32