


Part number

KI 1643 IB6



Interlocked switched socket-outlet, IB6 series, 2 poles + PE, 4 h (yellow), 16 A, 100 ÷ 130 V, sectionable fuse carrier 10 x 38 mm

Product description

Product type	Interlocked switched socket-outlet
Series	KI...IB6
N. of poles	2 poles + 
Clock position	4
Size	114x228 fixing plates FC xx41 TB
Cable entry	M25
Specification	Sectionable fuse carrier 10 x 38 mm

Technical data

Current	16 A
Voltage	100 ÷ 130 V
IP degree of protection	IP66

Further technical details

Weight	938,00 g
Operating temperature range (min, max)	-25°C ... +40°C
IK rating (impact degree of protection)	IK10

Material properties

Colour	RAL 7035 grey, RAL 1021 yellow
RoHs conformity	Compliant with exemption 6(c): copper alloy containing up to 4% lead by weight
China RoHs - EFUP	50
REACH SVHC substances	Yes Lead
SCIP number	F6799547-ab84-42f2-938f-233ba663766d

Approvals / Standards

Reference standard	EN 60309-1, -2 e -4
---------------------------	---------------------

General ordering information

EAN13 code	8015747199407
-------------------	---------------

Packaging Information

Packaging length	520,00 mm
Packaging height	305,00 mm
Packaging width	490,00 mm
Packaging weight	14,85 kg
Packaging volume	77,71 dm ³
Packaging description	Carton box
Packaging quantity	15 Pcs
Packaging EAN code	8015747230919
Sub-packaging length	270,00 mm
Sub-packaging height	125,00 mm
Sub-packaging width	120,00 mm
Sub-packaging weight	0,99 kg
Sub-packaging volume	4,05 dm ³
Sub-packaging description	Carton box
Sub-packaging quantity	1 Pcs
Sub-packaging EAN barcode	8015747230926