

Part number

MHON 16.32



Hood, LS-TYPE series, with 4 pegs, M32 side cable entry, size "77.27"

Product description

Product type	Hood
Series	LS-TYPE
Closing type	With 4 pegs
Size	Size 77.27
Cable entry	Side cable entry M32

Technical data

IP degree of protection	IP65
--------------------------------	------

Further technical details

Weight	175,00 g
Operating temperature range (min, max)	-40°C...+125°C

Material properties

Colour	RAL 9005 black
RoHs conformity	Compliant
China RoHs - EFUP	E
REACH SVHC substances	No

Approvals / Standards

Certifications	DNV, BV
UL	ECBT2
cUL	ECBT8

General ordering information

EAN13 code	8015747194266
eCl@ss 8.1	27440202
ETIM 7.0	EC000437

Packaging Information

Sub-packaging weight	0,88 kg
Sub-packaging description	Plastic packaging
Sub-packaging quantity	5 Pcs
Sub-packaging EAN barcode	8015747194273

Part number MHON 16.32



Catalogue drawings



Catalogue drawings

CH..N - MA, MF..N enclosures size "77.27" **LS-TYPE version**

inserts:

CD	40 poles + @	49+52 *
CT, CTS **)	40 poles + @	56 *
CDD	72 poles + @	62+65 *
CDE	32 poles + @	82+84 *
CSH	16 poles + @	90+92 *
CCE	16 poles + @	98+102 *
CNE, CSE, JCNE, JCSE	16 poles + @	99 and 108 *
CSS	16 poles + @	120+122 *
CTE, CTSE **)	16 poles + @	128 *
CMSE	6+2 (aux) poles + @	137 *
CMCE	6+2 (aux) poles + @	136 *
CP	6 poles + @	149+150 *
CX	6/36 e 12/2 poles + @	152+153 *
CX	4/0 e 4/2 poles + @	154 *
MIXO	4 modules	160-195 *

insert centre distance: 77,5 x 27 mm
* refer to catalogue page CN.12

description	part no.		entry	
			M	M
bulkhead mounting housing, with 2 levers	CHIN 16			
surface mounting housing, high construction, with 2 levers	MAPN 16.32	32		
with pegs, side entry				MHON 16.32 32
with pegs, side entry, high construction				MFON 16.32 32
with pegs, top entry				MHVN 16.32 32
with pegs, top entry, high construction				MFVN 16.32 32

** only in the CHIN 16 enclosure

panel cut-out for bulkhead mounting housing in mm

- kiln powder coating with RAL 9005 black epoxy polyester powder
- RAL 9005 black self-extinguishing thermoplastic locking lever (spare lever page 12)

dimensions shown are not binding and may be changed without notice

housings with double lever

hoods with 4 pegs

CHIN 16 dimensions in mm

MAPN 16.32 dimensions in mm

MHON 16.32 dimensions in mm

MFON 16.32 dimensions in mm

MHVN 16.32 dimensions in mm

MFVN 16.32 dimensions in mm