

Part number

MHVN 06 L25



Hood, LS-TYPE series, with 2 pegs, M25 top cable entry, size "44.27"

Product description

Product type	Hood
Series	LS-TYPE
Closing type	With 2 pegs
Size	Size 44.27
Cable entry	Top cable entry M25

Technical data

IP degree of protection	IP65
--------------------------------	------

Further technical details

Weight	84,00 g
Operating temperature range (min, max)	-40°C...+125°C

Material properties

Colour	RAL 9005 black
RoHs conformity	Compliant
China RoHs - EFUP	E
REACH SVHC substances	No

Approvals / Standards

Certifications	DNV, BV
UL	ECBT2
cUL	ECBT8

General ordering information

EAN13 code	8015747194204
eCl@ss 8.1	27440202
ETIM 7.0	EC000437

Packaging Information

Sub-packaging weight	0,42 kg
Sub-packaging description	Plastic packaging
Sub-packaging quantity	5 Pcs
Sub-packaging EAN barcode	8015747123341

Part number MHVN 06 L25



Catalogue drawings



Catalogue drawings

CH..N - MA, MF..N enclosures size "44.27" LS-TYPE version

<p>inserts: page</p> <p>CDD 24 poles + ⊕ 59 *</p> <p>CQE 10 poles + ⊕ 80 *</p> <p>CSH 6 poles + ⊕ 88 *</p> <p>CCE 6 poles + ⊕ 94 *</p> <p>CNE, CSE, JONE, JOSE 6 poles + ⊕ 95 and 103 *</p> <p>CSS 6 poles + ⊕ 118 *</p> <p>CTE, CTSE **) 6 poles + ⊕ 126 *</p> <p>MIXO 2 modules 160+195 *</p> <p>insert centre distance: 44 x 27 mm</p> <p>* refer to catalogue page CN.12</p>	<p> housings with single lever</p>	<p> hoods with 2 pegs</p>																														
<table border="0" style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th style="text-align: left; border-bottom: 1px solid black;">description</th> <th style="text-align: left; border-bottom: 1px solid black;">part no.</th> <th style="text-align: left; border-bottom: 1px solid black;">entry</th> </tr> </thead> <tbody> <tr> <td style="border-bottom: 1px solid black;">bulkhead mounting housing, with lever</td> <td style="border-bottom: 1px solid black;">CHIN 06 L</td> <td style="border-bottom: 1px solid black;">M</td> </tr> <tr> <td style="border-bottom: 1px solid black;">surface mounting housing, high construction, with lever</td> <td style="border-bottom: 1px solid black;">MAPN 06 L32</td> <td style="border-bottom: 1px solid black;">32</td> </tr> <tr> <td style="border-bottom: 1px solid black;">with pegs, side entry</td> <td></td> <td></td> </tr> <tr> <td style="border-bottom: 1px solid black;">with pegs, side entry, high construction</td> <td></td> <td></td> </tr> <tr> <td style="border-bottom: 1px solid black;">with pegs, top entry</td> <td></td> <td></td> </tr> <tr> <td style="border-bottom: 1px solid black;">with pegs, top entry, high construction</td> <td></td> <td></td> </tr> </tbody> </table>	description	part no.	entry	bulkhead mounting housing, with lever	CHIN 06 L	M	surface mounting housing, high construction, with lever	MAPN 06 L32	32	with pegs, side entry			with pegs, side entry, high construction			with pegs, top entry			with pegs, top entry, high construction			<table border="0" style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th style="text-align: left; border-bottom: 1px solid black;">part no.</th> <th style="text-align: left; border-bottom: 1px solid black;">entry</th> </tr> </thead> <tbody> <tr> <td style="border-bottom: 1px solid black;">MHON 06 L25</td> <td style="border-bottom: 1px solid black;">25</td> </tr> <tr> <td style="border-bottom: 1px solid black;">MFON 06 L25</td> <td style="border-bottom: 1px solid black;">25</td> </tr> <tr> <td style="border-bottom: 1px solid black;">MHVN 06 L25</td> <td style="border-bottom: 1px solid black;">25</td> </tr> <tr> <td style="border-bottom: 1px solid black;">MFVN 06 L25</td> <td style="border-bottom: 1px solid black;">25</td> </tr> </tbody> </table>	part no.	entry	MHON 06 L25	25	MFON 06 L25	25	MHVN 06 L25	25	MFVN 06 L25	25
description	part no.	entry																														
bulkhead mounting housing, with lever	CHIN 06 L	M																														
surface mounting housing, high construction, with lever	MAPN 06 L32	32																														
with pegs, side entry																																
with pegs, side entry, high construction																																
with pegs, top entry																																
with pegs, top entry, high construction																																
part no.	entry																															
MHON 06 L25	25																															
MFON 06 L25	25																															
MHVN 06 L25	25																															
MFVN 06 L25	25																															
<p>**) only in the CHIN 06 L enclosure</p> <p>panel cut-out for bulkhead mounting housing in mm</p> <p>- kiln powder coating with RAL 9005 black epoxy polyester powder - RAL 9005 black self-extinguishing thermoplastic locking lever (spare lever page 12)</p> <div style="text-align: center; margin-top: 10px;"> </div> <p style="font-size: small;">dimensions shown are not binding and may be changed without notice</p>	<p> dimensions in mm</p> <p>CHIN 06 L</p> <p>MAPN 06 L32</p>	<p> dimensions in mm</p> <p>MFON 06 L25</p> <p>MFVN 06 L25</p> <p>MHON 06 L25</p> <p>MHVN 06 L25</p>																														