

Part number

MHVN 06 LG25



Hood, LS-TYPE series, with 1 lever, M25 top cable entry, size "44.27"


| Product description | | Material properties | |
|---|------------------------|----------------------------------|--------------------------------------|
| Product type | Hood | Other materials | Lever: Polyamide (PA) Gasket: NBR |
| Series | LS-TYPE | Colour | RAL 9005 black |
| Closing type | With 1 lever | RoHs conformity | Compliant |
| Size | Size 44.27 | China RoHs - EFUP | E |
| Cable entry | Top cable entry M25 | REACH SVHC substances | No |
| Technical data | | Approvals / Standards | |
| IP degree of protection | IP65 | Certifications | DNV, BV |
| Further technical details | | UL | ECBT2 |
| Weight | 124,00 g | cUL | ECBT8 |
| Operating temperature range (min, max) | -40°C...+125°C | General ordering information | |
| | | EAN13 code | 8015747194341 |
| | | eCl@ss 8.1 | 27440202 |
| | | ETIM 7.0 | EC000437 |
| | | Packaging Information | |
| | | Sub-packaging weight | 0,62 kg |
| | | Sub-packaging description | Plastic packaging |
| | | Sub-packaging quantity | 5 Pcs |
| | | Sub-packaging EAN barcode | 8015747194358 |

Part number

MHVN 06 LG25



Catalogue drawings



Catalogue drawings

| CH..N - MF..N enclosures | | size "44.27" | LS-TYPE version | | | | | | | | | | | | | | | | | | | | | |
|---|---|--|-----------------|-----|--------------|------|-----|-------------|------|-----|-------------|------|----------------------|------------------------|-------|-----|-------------|-------|------|-----------|-----------|--------------------------|---------------|--|
| <p>inserts:</p> <table border="0"> <tr> <td>CDD</td> <td>24 poles + @</td> <td>59 *</td> </tr> <tr> <td>CQE</td> <td>10 poles + @</td> <td>80 *</td> </tr> <tr> <td>CSH</td> <td>6 poles + @</td> <td>88 *</td> </tr> <tr> <td>CCE</td> <td>6 poles + @</td> <td>94 *</td> </tr> <tr> <td>CNE, CSE, JONE, JCSE</td> <td>6 poles + @ 95 and 103</td> <td>118 *</td> </tr> <tr> <td>CSS</td> <td>6 poles + @</td> <td>118 *</td> </tr> <tr> <td>MIXO</td> <td>2 modules</td> <td>160+195 *</td> </tr> </table> <p>insert centre distance: 44 x 27 mm</p> <p>* refer to catalogue page CN.12</p> | CDD | 24 poles + @ | 59 * | CQE | 10 poles + @ | 80 * | CSH | 6 poles + @ | 88 * | CCE | 6 poles + @ | 94 * | CNE, CSE, JONE, JCSE | 6 poles + @ 95 and 103 | 118 * | CSS | 6 poles + @ | 118 * | MIXO | 2 modules | 160+195 * | <p>hoods with 2 pegs</p> | <p>covers</p> | |
| CDD | 24 poles + @ | 59 * | | | | | | | | | | | | | | | | | | | | | | |
| CQE | 10 poles + @ | 80 * | | | | | | | | | | | | | | | | | | | | | | |
| CSH | 6 poles + @ | 88 * | | | | | | | | | | | | | | | | | | | | | | |
| CCE | 6 poles + @ | 94 * | | | | | | | | | | | | | | | | | | | | | | |
| CNE, CSE, JONE, JCSE | 6 poles + @ 95 and 103 | 118 * | | | | | | | | | | | | | | | | | | | | | | |
| CSS | 6 poles + @ | 118 * | | | | | | | | | | | | | | | | | | | | | | |
| MIXO | 2 modules | 160+195 * | | | | | | | | | | | | | | | | | | | | | | |
| <p>description</p> <p>with lever and gasket, top entry with lever and gasket, top entry, high construction</p> <p>covers with pegs covers with lever</p> | <p>part no.</p> <p>entry M</p> <p>MHVN 06 LG25 25 MFVN 06 LG25 25</p> | <p>part no.</p> <p>CHCN 06 L CHCN 06 LG</p> | | | | | | | | | | | | | | | | | | | | | | |
| | <p>dimensions in mm</p> <p>MHVN 06 LG25</p> <p>MFVN 06 LG25</p> | <p>dimensions in mm</p> <p>CHCN 06 L</p> <p>CHCN 06 LG</p> | | | | | | | | | | | | | | | | | | | | | | |
| <p>- kiln powder coating with RAL 9005 black epoxy polyester powder - RAL 9005 black self-extinguishing thermoplastic locking lever (spare lever page 12)</p> | | | | | | | | | | | | | | | | | | | | | | | | |
| <p>IP65</p> <p>dimensions shown are not binding and may be changed without notice</p> | | | | | | | | | | | | | | | | | | | | | | | | |