


Part number

PE 16114 SV



Mobile plug, PLUSO series, 3 poles + PE, 11 h (red), 16 A, 440 ÷ 460 V, straight

Product description

| | |
|------------------------|---|
| Product type | Plug Mobile |
| Series | PE...SV, PLUSO |
| Connection type | Screw terminal connection |
| N. of poles | 3 poles +  |
| Clock position | 11 |
| Specification | Straight |

Technical data

| | |
|---|-----------------|
| Current | 16 A |
| Voltage | 440 ÷ 460 V |
| IP degree of protection | IP44 |
| Further technical details | |
| Weight | 126,00 g |
| Operating temperature range (min, max) | -25°C ... +40°C |

Material properties

| | |
|------------------------------|--|
| Colour | RAL 7035 grey, RAL 3000 red |
| RoHs conformity | Compliant with exemption 6(c): copper alloy containing up to 4% lead by weight |
| China RoHs - EFUP | 50 |
| REACH SVHC substances | Yes Lead |
| SCIP number | Ca7de37f-add8-4b77-9861-279c94903ade |

Approvals / Standards

| | |
|---------------------------|-------------------|
| Reference standard | EN 60309-1 and -2 |
|---------------------------|-------------------|

General ordering information

| | |
|-------------------|---------------|
| EAN13 code | 8015747062893 |
|-------------------|---------------|

Packaging Information

| | |
|------------------------------|----------------------|
| Packaging length | 208,00 mm |
| Packaging height | 140,00 mm |
| Packaging width | 290,00 mm |
| Packaging weight | 1,47 kg |
| Packaging volume | 8,44 dm ³ |
| Packaging description | Carton box |
| Packaging quantity | 10 Pcs |
| Packaging EAN code | 8015747234405 |

Part number

PE 16114 SV



Catalogue drawings

(16 / 32A) PE ... SV



| PE ... SV | A | B | Ø min | Ø max | |
|-----------------|--------|-------|-------|-------|----|
| 16A 2P+⊕ | 143,5 | 59 | 7 | 17 | |
| | 3P+⊕ | 148,5 | 66 | 7 | 17 |
| | 3P+N+⊕ | 167,5 | 75 | 9 | 22 |
| 32A 2P+⊕ | 187 | 80 | 9 | 22 | |
| | 3P+⊕ | 187 | 80 | 9 | 22 |
| | 3P+N+⊕ | 192,5 | 87 | 9 | 22 |