


Part number

PE 1634 PI



Flush-mounting socket outlet, PLUSO series, 3 poles + PE, 3 h (red), 16 A, 380 ÷ 380 V, inclined

Product description

| | |
|-----------------------|---|
| Product type | Socket Flush-mounting |
| Series | PE...PI, PLUSO |
| N. of poles | 3 poles +  |
| Clock position | 3 |
| Specification | Inclined |

Technical data

| | |
|--------------------------------|---------------------------|
| Current | 16 A |
| Voltage | 380V (50Hz.) 440V (60Hz.) |
| IP degree of protection | IP44 |

Further technical details

| | |
|---|-----------------|
| Operating temperature range (min, max) | -25°C ... +40°C |
|---|-----------------|

Material properties

| | |
|---------------|-----------------------------|
| Colour | RAL 7035 grey, RAL 3000 red |
|---------------|-----------------------------|

Approvals / Standards

| | |
|---------------------------|-------------------|
| Reference standard | EN 60309-1 and -2 |
|---------------------------|-------------------|

General ordering information

| | |
|-------------------|---------------|
| EAN13 code | 8015747154765 |
|-------------------|---------------|

Part number

PE 1634 PI



Catalogue drawings

(16 / 32A) PE ... PI



| PE ... PI | A | B | C | D | E | F | G | H | X | Y |
|-----------------|----|-----|-----|----|----|----|----|------|----|----|
| 16A 2P+⊕ | 64 | 82 | 82 | 38 | 46 | 52 | 62 | 30 | 52 | 60 |
| | 64 | 82 | 82 | 42 | 47 | 57 | 65 | 28 | 52 | 60 |
| | 92 | 100 | 100 | 43 | 47 | 66 | 78 | 37,5 | 77 | 85 |
| 32A 2P+⊕ | 92 | 100 | 100 | 40 | 55 | 68 | 76 | 35,5 | 77 | 85 |
| | 92 | 100 | 100 | 40 | 55 | 68 | 76 | 35,5 | 77 | 85 |
| | 92 | 102 | 102 | 43 | 55 | 74 | 86 | 39,5 | 77 | 85 |