


Part number

PE 1664 PV



Mobile socket outlet, PLUSO series, 3 poles + PE, 6 h (red), 16 A, 380 ÷ 415 V

Product description

| | |
|------------------------|---|
| Product type | Socket Mobile |
| Series | PE...PV, PLUSO |
| Connection type | Screw terminal connection |
| N. of poles | 3 poles +  |
| Clock position | 6 |

Technical data

| | |
|--------------------------------|-------------|
| Current | 16 A |
| Voltage | 380 ÷ 415 V |
| IP degree of protection | IP44 |

Further technical details

| | |
|---|-----------------|
| Weight | 150,00 g |
| Operating temperature range (min, max) | -25°C ... +40°C |

Material properties

| | |
|------------------------------|--|
| Colour | RAL 7035 grey, RAL 3000 red |
| RoHs conformity | Compliant with exemption 6(c): copper alloy containing up to 4% lead by weight |
| China RoHs - EFUP | 50 |
| REACH SVHC substances | Yes Lead |
| SCIP number | Ca7de37f-add8-4b77-9861-279c94903ade |

Approvals / Standards

| | |
|---------------------------|-------------------|
| Reference standard | EN 60309-1 and -2 |
|---------------------------|-------------------|

General ordering information

| | |
|-------------------|---------------|
| EAN13 code | 8015747064651 |
|-------------------|---------------|

Packaging Information

| | |
|------------------------------|-----------------------|
| Packaging length | 400,00 mm |
| Packaging height | 310,00 mm |
| Packaging width | 670,00 mm |
| Packaging weight | 16,70 kg |
| Packaging volume | 83,08 dm ³ |
| Packaging description | Carton box |
| Packaging quantity | 100 Pcs |
| Packaging EAN code | 8015747064668 |


Part number

PE 1664 PV



Catalogue drawings

(16 / 32A) PE ... PV



| PE...PV | A | B | ø min | ø max |
|-----------------|-----|------|-------|-------|
| 16A 2P+⊕ | 146 | 74,5 | 7 | 16 |
| 3P+⊕ | 146 | 84,5 | 7 | 16 |
| 3P+N+⊕ | 146 | 92,5 | 8 | 24 |
| 32A 2P+⊕ | 163 | 102 | 8 | 24 |
| 3P+⊕ | 163 | 102 | 8 | 24 |
| 3P+N+⊕ | 163 | 105 | 8 | 24 |