


Part number

# PE 3245 PV



Mobile socket outlet, PLUSO series, 3 poles + N + PE, 4 h (yellow), 32 A, 57/100 ÷ 75/130 V

#### Product description

<b>Product type</b>	Socket Mobile
<b>Series</b>	PE...PV, PLUSO
<b>N. of poles</b>	3 poles + N + 
<b>Clock position</b>	4

#### Technical data

<b>Current</b>	32 A
<b>Voltage</b>	57/100 ÷ 75/130 V
<b>IP degree of protection</b>	IP44

#### Further technical details

<b>Weight</b>	261,50 g
<b>Operating temperature range (min, max)</b>	-25°C ... +40°C

#### Material properties

<b>Colour</b>	RAL 7035 grey, RAL 1021 yellow
<b>RoHs conformity</b>	Compliant with exemption 6(c): copper alloy containing up to 4% lead by weight
<b>China RoHs - EFUP</b>	50
<b>REACH SVHC substances</b>	Yes Lead
<b>SCIP number</b>	Ca7de37f-add8-4b77-9861-279c94903ade

#### Approvals / Standards

<b>Reference standard</b>	EN 60309-1 and -2
---------------------------	-------------------

#### General ordering information

<b>EAN13 code</b>	8015747067003
-------------------	---------------

#### Packaging Information

<b>Packaging length</b>	275,00 mm
<b>Packaging height</b>	230,00 mm
<b>Packaging width</b>	275,00 mm
<b>Packaging weight</b>	2,95 kg
<b>Packaging volume</b>	17,39 dm <sup>3</sup>
<b>Packaging description</b>	Carton box
<b>Packaging quantity</b>	10 Pcs
<b>Packaging EAN code</b>	8015747067010

Part number

# PE 3245 PV



Catalogue drawings

(16 / 32A) PE ... PV



PE...PV	A	B	Ø min	Ø max	
<b>16A</b> 2P+⊕	157,5	68	7	17	
	3P+⊕	164,5	76	7	17
	3P+N+⊕	183,5	83	9	22
<b>32A</b> 2P+⊕	200,5	87	9	22	
	3P+⊕	200,5	87	9	22
	3P+N+⊕	200,5	91	9	22