

Part number

# PEW 3233 SI



Flush-mounting plug, PLUSO series, 2 poles + PE, 3 h (white), 32 A, 50 ÷ 250 V

## Product description

|                |                                                                                             |
|----------------|---------------------------------------------------------------------------------------------|
| Product type   | Plug<br>Flush-mounting                                                                      |
| Series         | PEW...SI, PLUSO                                                                             |
| N. of poles    | 2 poles +  |
| Clock position | 3                                                                                           |

## Technical data

|                         |              |
|-------------------------|--------------|
| Current                 | 32 A         |
| Voltage                 | > 50 ÷ 250 V |
| IP degree of protection | IP67         |

## Further technical details

|                                        |                 |
|----------------------------------------|-----------------|
| Operating temperature range (min, max) | -25°C ... +40°C |
|----------------------------------------|-----------------|

## Material properties

|        |                               |
|--------|-------------------------------|
| Colour | RAL 7035 grey, RAL 9010 white |
|--------|-------------------------------|

## Approvals / Standards

|                    |                   |
|--------------------|-------------------|
| Reference standard | EN 60309-1 and -2 |
|--------------------|-------------------|

## General ordering information

|            |               |
|------------|---------------|
| EAN13 code | 8015747157780 |
|------------|---------------|


Part number

# PEW 3233 SI



Catalogue drawings

(16 / 32A) PEW ... SI



| PEW ... SI |        | A  | B   | C   | D   | E  | F  | G    | H   | X  | Y  |
|------------|--------|----|-----|-----|-----|----|----|------|-----|----|----|
| <b>16A</b> | 2P+⊕   | 65 | 82  | 126 | 81  | 41 | 43 | 21,5 | 70  | 52 | 60 |
|            | 3P+⊕   | 65 | 82  | 126 | 81  | 47 | 43 | 24,5 | 78  | 52 | 60 |
|            | 3P+N+⊕ | 90 | 100 | 146 | 93  | 54 | 60 | 27,5 | 86  | 77 | 85 |
| <b>32A</b> | 2P+⊕   | 90 | 100 | 160 | 101 | 55 | 60 | 27,5 | 92  | 77 | 85 |
|            | 3P+⊕   | 90 | 100 | 160 | 101 | 55 | 60 | 27,5 | 92  | 77 | 85 |
|            | 3P+N+⊕ | 90 | 100 | 160 | 101 | 62 | 60 | 27,5 | 100 | 77 | 85 |