


Part number

SQE 3243.5



Interlocked switched socket-outlet, SQE series, 2 poles + PE, 4 h (yellow), 32 A, 100 ÷ 130 V, without fuse-carrier

| Product description | | Material properties | |
|--|---|----------------------------------|--|
| Product type | Interlocked switched socket-outlet | Colour | RAL 7035 grey, RAL 1021 yellow |
| Series | SQE | | Compliant with exemption 6(c): copper alloy containing up to 4% lead by weight |
| N. of poles | 2 poles +  | RoHs conformity | 6(c): copper alloy containing up to 4% lead by weight |
| Clock position | 4 | China RoHs - EFUP | 50 |
| Size | Socket fixing centre distance 88 x 230 mm | REACH SVHC substances | Yes Lead |
| Specification | Without fuse-carrier | SCIP number | Ce861c8d-b979-403b-96d9-80aef6dc281d |
| Technical data | | Approvals / Standards | |
| Current | 32 A | Reference standard | EN 60309-1, -2 e -4 |
| Voltage | 100 ÷ 130 V | General ordering information | |
| IP degree of protection | IP55 | EAN13 code | 8015747086455 |
| Further technical details | | Packaging Information | |
| Weight | 608,00 g | Sub-packaging length | 116,00 mm |
| Operating temperature range (min, max) | -25°C ... +40°C | Sub-packaging height | 103,00 mm |
| IK rating (impact degree of protection) | IK08 | Sub-packaging width | 230,00 mm |
| | | Sub-packaging weight | 0,61 kg |
| | | Sub-packaging volume | 2,75 dm ³ |
| | | Sub-packaging description | Carton box |
| | | Sub-packaging quantity | 1 Pcs |
| | | Sub-packaging EAN barcode | 8015747086462 |

Part number

SQE 3243.5



Catalogue drawings



Catalogue drawings



| SQE.5 | | A |
|-------|--------|-----|
| 32A | 2P+⊕ | 92 |
| | 3P+⊕ | 92 |
| | 3P+N+⊕ | 100 |