


Part number

# SQV 3223.5



Interlocked switched socket-outlet, SQV series, 2 poles + PE, 2 h (green), 32 A, > 50 V, sectionable fuse carrier 10 x 38 mm

#### Product description

|                       |   |
|-----------------------|---|
| <b>Product type</b>   | Interlocked switched socket-outlet  |
| <b>Series</b>         | SQV   |
| <b>N. of poles</b>    | 2 poles +  |
| <b>Clock position</b> | 2   |
| <b>Specification</b>  | Sectionable fuse carrier 10 x 38 mm   |

#### Technical data

|                                |        |
|--------------------------------|--------|
| <b>Current</b>                 | 32 A   |
| <b>Voltage</b>                 | > 50 V |
| <b>IP degree of protection</b> | IP55   |

#### Further technical details

|  |                 |
|--|-----------------|
| <b>Operating temperature range (min, max)</b>  | -25°C ... +40°C |
| <b>IK rating (impact degree of protection)</b> | IK08            |

#### Material properties

|               |                               |
|---------------|-------------------------------|
| <b>Colour</b> | RAL 7035 grey, RAL 6017 green |
|---------------|-------------------------------|

#### Approvals / Standards

|                           |                     |
|---------------------------|---------------------|
| <b>Reference standard</b> | EN 60309-1, -2 e -4 |
|---------------------------|---------------------|

#### General ordering information

|                   |               |
|-------------------|---------------|
| <b>EAN13 code</b> | 8015747160360 |
|-------------------|---------------|

Part number

# SQV 3223.5



Catalogue drawings



Catalogue drawings



| SQV.5 |        | A   |
|-------|--------|-----|
| 32A   | 2P+⊕   | 92  |
|       | 3P+⊕   | 92  |
|       | 3P+N+⊕ | 100 |