

Part number

# TM 16114 SP



Interlocked switched socket-outlet, TM series,  
3 poles + PE, 11 h (red), 16 A, 440 ÷ 460 V,  
without fuse-carrier, with base box

#### Product description

|                       |                                                                                             |
|-----------------------|---------------------------------------------------------------------------------------------|
| <b>Product type</b>   | Interlocked switched socket-outlet                                                          |
| <b>Series</b>         | TM..SP/KSP                                                                                  |
| <b>N. of poles</b>    | 3 poles +  |
| <b>Clock position</b> | 11                                                                                          |
| <b>Specification</b>  | Without fuse-carrier<br>With base box                                                       |

#### Technical data

|                                |             |
|--------------------------------|-------------|
| <b>Current</b>                 | 16 A        |
| <b>Voltage</b>                 | 440 ÷ 460 V |
| <b>IP degree of protection</b> | IP66 / IP67 |

#### Further technical details

|                                                |                 |
|------------------------------------------------|-----------------|
| <b>Operating temperature range (min, max)</b>  | -25°C ... +40°C |
| <b>UL 94 flammability rating</b>               | V-2             |
| <b>IK rating (impact degree of protection)</b> | IK10            |

#### Material properties

|               |                             |
|---------------|-----------------------------|
| <b>Colour</b> | RAL 7012 grey, RAL 3000 red |
|---------------|-----------------------------|

#### Approvals / Standards

|                           |                     |
|---------------------------|---------------------|
| <b>Reference standard</b> | EN 60309-1, -2 e -4 |
|---------------------------|---------------------|

#### General ordering information



|                   |               |
|-------------------|---------------|
| <b>EAN13 code</b> | 8015747160667 |
|-------------------|---------------|

Part number

# TM 16114 SP



Catalogue drawings



|               | A   | B   |
|---------------|-----|-----|
| <b>2P+⊕</b>   | 133 | 276 |
| <b>3P+⊕</b>   | 135 | 276 |
| <b>3P+N+⊕</b> | 140 | 277 |