


Part number

TM 1665 ISX



Interlocked switched socket-outlet, TM series, 3 poles + N + PE, 6 h (red), 16 A, 200/346 ÷ 240/415 V, sectionable fuse carrier 10 x 38 mm, with base box

Product description

Product type	Interlocked switched socket-outlet
Series	TM ATEX
N. of poles	3 poles + N + 
Clock position	6
Size	114 x 255 mm fixing distance, for assembly in plates TM xx45 TB
Specification	Sectionable fuse carrier 10 x 38 mm With base box

Technical data

Current	16 A
Voltage	200/346 ÷ 240/415 V
IP degree of protection	IP66 / IP67

Further technical details

Weight	1.620,00 g
Operating temperature range (min, max)	-25°C ... +40°C
UL 94 flammability rating	V-2
IK rating (impact degree of protection)	IK10

Material properties

Colour	RAL 7012 grey, RAL 3000 red
RoHs conformity	Compliant with exemption 6(c): copper alloy containing up to 4% lead by weight
China RoHs - EFUP	50
REACH SVHC substances	Yes Lead
SCIP number	Ce861c8d-b979-403b-96d9-80aef6dc281d

Approvals / Standards

Reference standard	EN 60309-1, -2 e -4
---------------------------	---------------------

General ordering information

EAN13 code	8015747103251
-------------------	---------------

Packaging Information

Packaging weight	14,58 kg
Packaging volume	55,44 dm ³
Packaging description	Carton box
Packaging quantity	9 Pcs
Packaging EAN code	8015747103268
Sub-packaging weight	1,62 kg
Sub-packaging description	Plastic packaging
Sub-packaging quantity	1 Pcs
Sub-packaging EAN barcode	8015747103275