


Part number

TM 32104KSP



Interlocked switched socket-outlet, TM series,
3 poles + PE, 10 h (green), 32 A, > 50 V,
without fuse-carrier, with base box

Product description		Material properties	
Product type	Interlocked switched socket-outlet	Colour	RAL 7012 grey, RAL 6017 green
Series	TM..SP/KSP		Compliant with exemption 6(c): copper alloy containing up to 4% lead by weight
N. of poles	3 poles + 	RoHs conformity	6(c): copper alloy containing up to 4% lead by weight
Clock position	10	China RoHs - EFUP	50
Specification	Without fuse-carrier With base box	REACH SVHC substances	Yes Lead
Technical data		SCIP number	Ce861c8d-b979-403b-96d9-80aef6dc281d
Current	32 A	Approvals / Standards	
Voltage	> 50 V	Reference standard	EN 60309-1, -2 e -4
IP degree of protection	IP66 / IP67	General ordering information	
Further technical details		EAN13 code	8015747161909
Weight	1.380,00 g	Packaging Information	
Operating temperature range (min, max)	-25°C ... +40°C	Packaging length	385,00 mm
UL 94 flammability rating	V-2	Packaging height	320,00 mm
IK rating (impact degree of protection)	IK10	Packaging width	485,00 mm
		Packaging weight	12,52 kg
		Packaging volume	59,75 dm ³
		Packaging description	Carton box
		Packaging quantity	9 Pcs
		Packaging EAN code	8015747275781
		Sub-packaging weight	1,39 kg
		Sub-packaging description	Carton tray
		Sub-packaging quantity	1 Pcs
		Sub-packaging EAN barcode	8015747275774

Part number

TM 32104KSP



Catalogue drawings



	A	B
2P+⊕	133	276
3P+⊕	135	276
3P+N+⊕	140	277