


Part number

TM 3234KSP



Interlocked switched socket-outlet, TM series,
3 poles + PE, 3 h (red), 32 A, 380 ÷ 380 V,
without fuse-carrier, with base box

Product description	
Product type	Interlocked switched socket-outlet
Series	TM..SP/KSP
N. of poles	3 poles + 
Clock position	3
Specification	Without fuse-carrier With base box
Technical data	
Current	32 A
Voltage	380V (50Hz.) 440V (60Hz.)
IP degree of protection	IP66 / IP67
Further technical details	
Weight	1.400,00 g
Operating temperature range (min, max)	-25°C ... +40°C
UL 94 flammability rating	V-2
IK rating (impact degree of protection)	IK10

Material properties	
Colour	RAL 7012 grey, RAL 3000 red
RoHs conformity	Compliant with exemption 6(c): copper alloy containing up to 4% lead by weight
China RoHs - EFUP	50
REACH SVHC substances	Yes Lead
SCIP number	Ce861c8d-b979-403b-96d9-80aef6dc281d
Approvals / Standards	
Reference standard	EN 60309-1, -2 e -4
General ordering information	
EAN13 code	8015747137188
Packaging Information	
Packaging length	385,00 mm
Packaging height	320,00 mm
Packaging width	485,00 mm
Packaging weight	12,60 kg
Packaging volume	59,75 dm ³
Packaging description	Carton box
Packaging quantity	9 Pcs
Packaging EAN code	8015747137249
Sub-packaging weight	1,40 kg
Sub-packaging description	Carton tray
Sub-packaging quantity	1 Pcs
Sub-packaging EAN barcode	8015747137256

Part number

TM 3234KSP



Catalogue drawings



	A	B
2P+⊕	133	276
3P+⊕	135	276
3P+N+⊕	140	277