

Part number

TM 3264KSSP



Interlocked switched socket-outlet, TM series,
3 poles + PE, 6 h (red), 32 A, 380 ÷ 415 V,
without fuse-carrier, without base box

| Product description | | Material properties | |
|--|--|----------------------------------|--|
| Product type | Interlocked switched socket-outlet | Colour | RAL 7012 grey, RAL 3000 red |
| Series | TM..SSP/KSSP | | Compliant with exemption 6(c): copper alloy containing up to 4% lead by weight |
| N. of poles | 3 poles + | RoHs conformity | |
| Clock position | 6 | China RoHs - EFUP | 50 |
| Size | 114 x 255 mm fixing distance, for assembly in single or multiple boxes | REACH SVHC substances | Yes Lead |
| Specification | Without fuse-carrier Without base box | SCIP number | Ce861c8d-b979-403b-96d9-80aef6dc281d |
| Technical data | | Approvals / Standards | |
| Current | 32 A | Reference standard | EN 60309-1, -2 e -4 |
| Voltage | 380 ÷ 415 V | General ordering information | |
| IP degree of protection | IP66 / IP67 | EAN13 code | 8015747126120 |
| Further technical details | | Packaging Information | |
| Weight | 1.100,00 g | Packaging length | 385,00 mm |
| Operating temperature range (min, max) | -25°C ... +40°C | Packaging height | 320,00 mm |
| UL 94 flammability rating | V-2 | Packaging width | 485,00 mm |
| IK rating (impact degree of protection) | IK10 | Packaging weight | 10,00 kg |
| | | Packaging volume | 59,75 dm ³ |
| | | Packaging description | Carton box |
| | | Packaging quantity | 9 Pcs |
| | | Packaging EAN code | 8015747126687 |
| | | Sub-packaging length | 95,00 mm |
| | | Sub-packaging height | 40,00 mm |
| | | Sub-packaging width | 253,00 mm |
| | | Sub-packaging weight | 1,11 kg |
| | | Sub-packaging volume | 0,96 dm ³ |
| | | Sub-packaging description | Carton tray |
| | | Sub-packaging quantity | 1 Pcs |
| | | Sub-packaging EAN barcode | 8015747126694 |