


Part number

TM 3293KSP



Interlocked switched socket-outlet, TM series,
2 poles + PE, 9 h (red), 32 A, 380 ÷ 415 V,
without fuse-carrier, with base box

| Product description | | Material properties | |
|--|---|----------------------------------|--|
| Product type | Interlocked switched socket-outlet | Colour | RAL 7012 grey, RAL 3000 red |
| Series | TM..SP/KSP | | Compliant with exemption 6(c): copper alloy containing up to 4% lead by weight |
| N. of poles | 2 poles +  | RoHs conformity | 6(c): copper alloy containing up to 4% lead by weight |
| Clock position | 9 | China RoHs - EFUP | 50 |
| Size | 115 x 450 x 18 mm | REACH SVHC substances | Yes Lead |
| Specification | Without fuse-carrier With base box | SCIP number | Ce861c8d-b979-403b-96d9-80aef6dc281d |
| Technical data | | Approvals / Standards | |
| Current | 32 A | Reference standard | EN 60309-1, -2 e -4 |
| Voltage | 380 ÷ 415 V | General ordering information | |
| IP degree of protection | IP66 / IP67 | EAN13 code | 8015747126229 |
| Further technical details | | Packaging Information | |
| Weight | 1.370,00 g | Packaging weight | 12,33 kg |
| Operating temperature range (min, max) | -25°C ... +40°C | Packaging volume | 55,44 dm ³ |
| UL 94 flammability rating | V-2 | Packaging description | Carton box |
| IK rating (impact degree of protection) | IK10 | Packaging quantity | 9 Pcs |
| | | Packaging EAN code | 8015747114844 |
| | | Sub-packaging weight | 1,37 kg |
| | | Sub-packaging description | Carton tray |
| | | Sub-packaging quantity | 1 Pcs |
| | | Sub-packaging EAN barcode | 8015747044189 |

Part number

TM 3293KSP



Catalogue drawings



| | A | B |
|----------------|-----|-----|
| 2P+ \oplus | 133 | 276 |
| 3P+ \oplus | 135 | 276 |
| 3P+N+ \oplus | 140 | 277 |