


Part number

TM 3295 IS



Interlocked switched socket-outlet, TM series, 3 poles + N + PE, 9 h (blue), 32 A, 120/208 ÷ 144/250 V, sectionable fuse carrier 14 x 51 mm, with base box

| Product description | | Material properties | |
|--|---|----------------------------------|--|
| Product type | Interlocked switched socket-outlet | Colour | RAL 7012 grey, RAL 5015 blue |
| Series | TM.. IS/KIS | | Compliant with exemption 6(c): copper alloy containing up to 4% lead by weight |
| N. of poles | 3 poles + N +  | RoHs conformity | 6(c): copper alloy containing up to 4% lead by weight |
| Clock position | 9 | China RoHs - EFUP | 50 |
| Size | 145 x 565 x 18 mm | REACH SVHC substances | Yes Lead |
| Specification | Sectionable fuse carrier 14 x 51 mm With base box | SCIP number | F6799547-ab84-42f2-938f-233ba663766d |
| Technical data | | Approvals / Standards | |
| Current | 32 A | Reference standard | EN 60309-1, -2 e -4 |
| Voltage | 120/208 ÷ 144/250 V | General ordering information | |
| IP degree of protection | IP66 / IP67 | EAN13 code | 8015747092227 |
| Further technical details | | Packaging Information | |
| Weight | 3.250,00 g | Sub-packaging length | 150,00 mm |
| Operating temperature range (min, max) | -25°C ... +40°C | Sub-packaging height | 188,00 mm |
| UL 94 flammability rating | V-2 | Sub-packaging width | 430,00 mm |
| IK rating (impact degree of protection) | IK10 | Sub-packaging weight | 3,25 kg |
| | | Sub-packaging volume | 12,13 dm ³ |
| | | Sub-packaging description | Carton box |
| | | Sub-packaging quantity | 1 Pcs |
| | | Sub-packaging EAN barcode | 8015747107617 |

Part number

TM 3295 IS



Catalogue drawings



| | A |
|---------------|----------|
| 2P+⊕ | 162 |
| 3P+⊕ | 162 |
| 3P+N+⊕ | 169 |